# TRICOR8





#### TRICOR8

8.4" Rugged Panel PC with Intel Atom Quad Core

#### **DESCRIPTION**

The TRICOR8 is a Rugged Panel PC with a built-in 8.4" screen and latest SBC. The system is constructed with , high strength, light weight Airborne HE30 grade aluminium alloy housing. Its modular architecture allows the system to be easily configurable with many options. The fanless design helps in noiseless operation, increases reliability, and gives the system a longer MTBF. The operational accessories such as MIL connectors have easy access. The TRICOR8 meets the MIL-STD-810F and MIL-STD461E standards, to suit any application that need a rugged solution .











### **TECHNICAL SPECIFICATIONS**

	-		
Processor	Intel® Atom Quad Core up to 3GHz Processor Speed.		
Graphic	HD-Graphic for Intel Atom		
Memory	8GB DDR3 ECC RAM, exp. Up to 32 GB		
Storage	512 GB SATA SSD		
Display	8.4" (Diagonal) TFT LCD Display, Resolution: 800x600 Display Color: 16M Colors, Brightness: 300 nits Viewing Angle: 170o, Analog Resistive Touch		
Keypad/ Switch	On Screen Display (OSD) Keypad , 1 x Power ON/OFF Switch		
MIL-DTL-38999 (series-III) Connectors	1 x 37-Pin Circular Connector (J1) 2 x USB Connector (On Front Panel) 1 x Gigabit Ethernet Connector (J2) 1 x RS232 Serial Connector (J3) 1 x 28V DC I/P Connector (J4)		
Power Input	115/230 VAC / 18-36 VDC input		
Power Consumption	<40W		
Software	Windows 10 Professional / RHEL 7 Workstation		
Dimensions	210mm x 210mm x 35mm (Front Panel) 170mm x 119mm x 106mm (Panel Cutout)		
Weight	5.0 Kgs +/- 0.5		
Shade	Light Admiralty Grey (Semi - Glossy) Powder Coated		
Material	Aluminum Alloy Construction		
Mounting	Panel Mount		
ENVIRONMENT	TEMPERATURE	Operating : -20°C to +60°C Storage : -40°C to +70°C	
	SHOCK	20g , 11ms	
	HUMIDITY	95% @ 40°C, Non-Condensing, Operating and Storage	
	ALTITUDE	Up to 15000 ft. Operating, Non-Operating	
	SALT FOG/SAND DUST	Unit is 100% Enclosed, Resistant to Salt Fog, Fungus	
	VIBRATION	2.25grms Random	
	EMI/EMC	MIL-STD461E	
	INGRESS PROTECTION	IP-65 on Front Panel	
OPTIONAL	TOUCH	Analog Resistive touch screen	



www.thrikasa.in

## **ORDERING INFORMATION:**

TRICOR8-RC-20-A-2-A-1-XX

SBC Description
CEC 20 Intel Atom

Ram Size	Decsription
Α	8GB
В	16GB
С	32GB

	Storage	Decsription
	1	256GB SSD
	2	512GB SSD

Add On Module	Decsription
1	Required
0	Not Required

Power	Decsription
Α	230V A/C I/P
В	18-36V DC I/P